

Drench™ Magic Coat Black

Premium water-based matt black coating for concrete, tarmac, brick & block.

PRODUCT DESCRIPTION

Drench™ Magic Coat Black is a premium water-based coating designed for the protection and enhancement of concrete, tarmac, brick and block surfaces. It provides a durable, uniform matt black finish with excellent coverage and low VOC content.

RECOMMENDED USES

Suitable substrates

- Concrete surfaces
- Tarmac and asphalt
- Brickwork
- Concrete blocks
- Masonry substrates

Typical applications

- Driveways
- Yard areas
- Agricultural buildings
- Boundary walls
- Industrial & commercial surfaces

PRODUCT INFORMATION

| Property | Value |
|---------------------|------------------------------|
| Colour | Black |
| Finish | Matt |
| Physical state | Liquid |
| Density | 1.13 g/cm ³ |
| Solids content | 45% |
| VOC content | <5 g/L |
| Application methods | Brush, Roller, Airless Spray |
| Cleaning | Water |
| Packaging | 15 L |

COVERAGE RATE

| Pack size | Coverage |
|-----------|----------------------------------|
| 15 Litres | Approximately 100 m ² |

Coverage may vary depending on substrate porosity and application method.

DRYING TIMES

At 20°C and 65% relative humidity.

| Stage | Time |
|-------------|-------------|
| Touch dry | 1 Hour |
| Recoat time | 4 Hours |
| Full cure | 24–48 Hours |

Low temperatures and high humidity may extend drying times.

SURFACE PREPARATION

All surfaces must be clean, dry, structurally sound, and free from dust, grease, oil, moss and loose material. Pressure washing is recommended where appropriate.

APPLICATION INSTRUCTIONS

1. Stir thoroughly before use.
2. Apply evenly using brush, roller or spray equipment.
3. Avoid application during rain or when rain is expected before drying.
4. Apply a second coat after 4 hours where increased durability or opacity is required.

STORAGE

Store between 5°C and 30°C. Protect from frost, direct sunlight and excessive heat. Keep containers tightly sealed when not in use.

HEALTH & SAFETY

Consult the Safety Data Sheet (SDS) before use.

- Avoid contact with eyes and skin.
- Wear suitable protective clothing.
- Ensure adequate ventilation during application.
- Keep out of reach of children.

ENVIRONMENTAL INFORMATION

- Water-based formulation
- Low VOC (<5 g/L)
- Suitable for professional and consumer use

PACKAGING

Available in 15 L containers.

MANUFACTURER

Paintex Limited T/A Drench
Dundalk, Co. Louth, Ireland

TECHNICAL DATA SUMMARY

| Property | Value |
|----------|-------|
| Colour | Black |

| | |
|-------------|--------------------------------|
| Density | 1.13 g/cm ³ |
| Solids | 45% |
| VOC | <5 g/L |
| Touch dry | 1 Hour |
| Recoat | 4 Hours |
| Coverage | 100 m ² per 15 L |
| Substrates | Concrete, Tarmac, Brick, Block |
| Application | Brush, Roller, Spray |